



Paint Effects

Canaan

Decorative effect for interior walls – rust look



Paint Effects

Genesis

Decorative effect for interior walls – concrete look



Canaan

Decorative effect for interior walls – rust look



Sample application: Timna 210 KC

Rust effect colors:



210KC

Timna



211KC

Etzion



212KC

Gazit



213KC

Tual

Safari Natural is also available in Neutrals shades in the shades spectrum fandeck



Genesis

Decorative effect for interior walls – concrete look



Sample application: Dusty concrete 112BA

Concrete effect colors:




111BA Chalk gray



112BA Dusty concrete



113BA Basalt black



114BA Lachish purple



115BA Natural clay



116BA Pottery red




117BA Arbel blue



118BA Tarsus green

Canaan Application Instructions:



Stage 1

Using a Tambour roller, paint the wall with a shade of Supercryl similar to the desired Canaan color.

We recommend frequently stepping back from the wall during the painting process to gauge the overall look.



Stage 2

a. To achieve a semi-transparent rust effect

Stir the Canaan paint well. Wet a viscose sponge with warm water until the whole sponge is soft and saturated. Wring it out well. Dip the sponge in a little bit of paint and spread on the wall, starting in the upper left-hand corner, using circular, arched motions, until the wall is completely covered.

Alternately, apply a thin layer of paint with a short-nap roller, and tap the paint lightly with a damp viscose sponge.

b. To achieve a semi-opaque to opaque rust effect

Stir the Canaan paint well. Apply the Canaan paint with a brush, using long top to bottom strokes. Smudge the edges until they are no longer visible. A second coat may be applied after approximately 2 hours.

c. To achieve an opaque look

Apply 2-3 coats with a roller.

Genesis Application Instructions:



Stage 1

Paint the wall with a shade of Supercryl similar to the desired Genesis color.



Stage 2

Apply 2 coats of Genesis paint with a short-nap roller. Make sure to eliminate air bubbles with the roller.

Stage 3

Dip a 3-4" wide brush in Genesis. Remove excess paint from the brush. Apply the paint using long, gentle, top to bottom strokes. We recommend frequently stepping back from the wall during the painting process to gauge the overall look.



Stage 4

After partial drying of the wall (i.e., there is no longer any gloss), go over the white spots with a dry brush to create the effect of the white, cloudy lines characteristic of concrete.

It is recommended to read the technical sheet of the product at Tambour website www.tambourpaints.com

www.tambourpaints.com

Tambour Ltd., P.O. Box 8488, Netania South Industrial Zone 42504.



Low VO

Tambour encourages green building

Tambour offers a wide range of products for walls, wood and metal, displaying the green label of the Standards Institute



YOUR IMAGINATION. OUR PAINT.

